



VBC COOL EX-8500V

Water soluble cutting, grinding fluid

Description EX-8500V is high performance mineral oil -based micro emulsion type water

soluble cutting fluids for general cutting processing.

Benefits 1.It has a good lubricity, anti-rust ability, anti-corrosion ability for nonferrous

metals, can be used to both aluminum and ferrous metals.

2.It has a good anti-decomposition ability, emulsification stability, anti-foaming

ability, cleaning ability.

Typical properties

Items	Results	Test mothod
Appearance, conc	Yellow	Visual
Appearance, 30vol%	Light yellow White translucent	Visual
Specific gravity, 15/4 ℃	0.993	ASTM D1298
pH, room temp, 5vol%	8.9 ~ 9.9	KS M 0011
Amine value (mgKOH/g)	77.7 ~ 87.7	KS M0065

^{*} Above test results are new fluid's typical properties, can be changed by quality improvement.

Application Aluminum metals: Milling, Turning, Drilling, Reamer, Grinding etc.

Ferrous metals: Milling, Turning, Drilling, Grinding etc.

Cutting, Grinding: 7~10% by refractometer

Concentrate's concentration *0.7= concentration by refractometer

Term of validity 12 months from the date of manufacture at sealed state, 0 to 40 °C.

Safety information

Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.

