

## VBC GEAR BHG- 100V

### EP type of industrial gear oil

**Description** **BHG-100V** oil is mineral oil based on EP type high performance gear oil

**Benefits**

1. High load carrying capacity and extreme pressor lubrication
2. Low pour point, Good water separability and foam characteristic.
3. Good oxidation stability and multi-metal compatibility.

**Typical properties**

| Test items                | Results      | Test method |
|---------------------------|--------------|-------------|
| Appearance, conc          | Light yellow | VISUAL      |
| Specific gravity,15/4°C   | 0.873        | ASTM D 1298 |
| Kin. viscosity, 40°C,cSt  | 100          | ASTM D 445  |
| Flash point, COC,°C, Min. | 234          | ASTM D 92   |
| Pour point,°C, Max.       | -20          | ASTM D 97   |
| Copper corosion           | 1B           | ASTM D 130  |

\*The test results are typical properties of fresh oil, can be changed by quality improvement.

**Application** Where EP type of of high performance industrial gear oil is need

**Term of validity** 12 months from the date of manufacture at sealed state, 0 to 40°C.

**Safety** Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.