

VBC GEAR BHG-320V

EP type of industrial gear oil

Description **BHG-320V** oil is mineral oil based on EP type high performance gear oil

- Benefits**
1. High load carrying capacity and extreme pressor lubrication
 2. Low pour point, Good water separability and foam characteristic.
 3. Good oxidation stability and multi-metal compatibility.

| Typical properties | Test items | Results | Test method |
|--------------------|----------------------------|-------------------|-------------|
| | Appearance, conc | Brown transparent | VISUAL |
| | Specific gravity, 15/4°C | 0.897 | ASTM D 1298 |
| | Kin. viscosity, 40°C, cSt | 320 | ASTM D 445 |
| | Flash point, COC, °C, Min. | 244 | ASTM D 92 |
| | Pour point, °C, Max. | -15 | ASTM D 97 |
| | Copper corosion | 1B | ASTM D 130 |

*The test results are typical properties of fresh oil, can be changed by quality improvement.

Application Where EP type of of high performance industrial gear oil is need

Term of validity 12 months from the date of manufacture at sealed state, 0 to 40°C.

Safety Refer to the our MSDS for safety information

The information contained and the recommendations made in this data sheet are based upon data collected and believed by us to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made herein with respect to the merchandise described and we assume no responsibility for the results or the use there of.